

JUTANET®

LIGHTER
SMARTER
GREENER
WRAP

lower net density
reduces plastic waste



JUTANET® represents a new level of round bale wrapping technology. Designed to meet the highest performance standards. Smarter net construction reduces density thus lowering the plastic footprint.



www.juta.cz

JUTA
the signature of assurance

How to make the plastics circular? The question is who can add value?

With its motto 'The signature of assurance' JUTA gives its customers the guarantee of outstanding products. To achieve this, JUTA is dedicated to continuous invention, innovation and investment in the latest technology and engineering.

Do not compromise on technology nor on objectives

The recommendations for users of our products are based on long-term experience with development, production, sales and use of the round bale net wrap.



Logistics efficiency Waste management

We are very aware of the need to reduce the environmental impact of our production processes, logistics and the use of the round bale net, and Green Wrap does just this.

An innovative product needs a clever consumer

One product of this investment is the new generation JUTANET Green Wrap. The success of Green Wrap is due to the weaving process, improved materials and new net design. The result is a net wrap that is lighter and stronger than standard net wraps available on the market.

Contribute It's a good start for the future with plastics

Green Wrap consists of 12% less plastic while still improving the performance of breaking strength compared to standard construction net wrap. Along with improved performance, Green Wrap has a smaller ecological footprint.

Type	Netto Weight/roll [kg]		Netto Weight/pallet [kg]		Rolls per pallet	Breaking strength [kgf]	
	Standard	Green Wrap	Standard	Green Wrap		Standard	Green Wrap
123, 125cm/2000m	21,6	19,0	345	304	16	270	270*
123, 125cm/2600m	28,1	24,5	450	392			
123, 125cm/3000m	32,4	28,5	518	456			
123, 125cm/3600m	38,9	34,2	622	547			
123, 125cm/4000m	43,2	38,0	691	608			
130cm/2000m	22,5	20,0	355	320			
130cm/2600m	29,2	26,0	467	416			
130cm/3000m	33,6	30,0	538	480			
130cm/3600m	40,3	36,0	645	576			

*improved strength/performance in real conditions

